


Quick-Tape

self-adhesive foam panel



Extruded polystyrene foam XPS

both sides coated with a special self-adhesive film, the adhesive parts are protected by silicon paper.

Special self-adhesive film

- o solvent-free, eco-friendly
- o high initial bonding strength, elastic joint
- o resistant to weather and ageing
- o special adhesive-film protected by silicon paper

Extruded polystyrene foam XPS

- o thermal conduction WLG035 (German classification)
- o specific weight 35Kg/m³
- o compression strength 0.30N/mm² (according to DIN 53421)
- o humidity-resistant
- o free of CFC and HCFC

Thickness	(mm)	17	20	21	22	24	25	26	30	40
U-value	(W/m ² x K)	1,53	1,35	1,29	1,25	1,17	1,13	1,09	0,97	0,76
Weight	(Kg/m ²)	0,7	0,8	0,8	0,9	0,9	1,0	1,0	1,1	1,4

Dimension: 3000x1000 mm

Other dimensions on request.

Quick-Tape is a pre-fabricated product intended to produce composite panels.

Installation and application guidelines must be strictly obeyed!

Our application technology references, installation and processing indications as well as the product specification data are only general guidelines to describe the condition and performance of our products and do not constitute a warranty in the legal sense (e.g. paragraph 443 of German Code BGB). Because of the huge variety of intended purposes and the respective special conditions the user's own aptitude testing is obligatory. Even application technology support does not release the user from his responsibility for the success and fitness for purpose of his work.

We reserve the right to implement changes in the sense of the technical progress